



	Q6 POWER CHAIR SERIES											REAR-WHEEL DRIVE	MID-WHEEL DRIVE	FRONT-WHEEL DRIVE
	Q6 EDGE [®] 2.0 <small>AVAILABLE WITH iLEVEL[®]</small>	Q6 EDGE [®]	Q6 EDGE [®] X	QUANTUM [®] 6000Z	QUANTUM [®] 610	Q6 EDGE [®] HD <small>AVAILABLE WITH 400 LBS. HEAVY DUTY LIFT</small>	QUANTUM [®] RIVAL [®]	J6	QUANTUM [®] 1450					
DRIVE WHEELS	14" Solid Optional: 14" Pneumatic	14" Solid Optional: 14" Pneumatic	14" Pneumatic or Solid (Call for availability)	14" Solid Optional: 14" Pneumatic	10" Solid Optional: 10" Pneumatic	14" Solid Optional: 14" Pneumatic	14" Solid Optional: 14" Pneumatic	10" Solid Optional: 10" Pneumatic	14" Solid					
CASTER WHEELS	Front: 6" Solid Rear: 6" Solid	Front: 6" Solid Rear: 6" Solid	Front: 6" Solid Rear: 6" Solid	Front: 6" Solid Rear: 6" Solid	Front: 5" Solid Rear: 6" Solid	Front: 6" Solid Rear: 6" Solid	Front: 9" Pneumatic	Front: 5" Solid Rear: 6" Solid	9" Solid					
ANTI-TIP WHEELS	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	4" Solid					
MAXIMUM SPEED ⁴	Up to 6 mph	Up to 5 mph (Optional: 6 mph)	Up to 6 mph	Up to 6 mph (Optional: 8 mph)	Up to 4 mph	Up to 4.7 mph	Up to 6 mph (Optional: 8 mph)	Up to 4 mph	Up to 4.5 mph					
GROUND CLEARANCE	2.7" (battery tray)	3" (frame center)	3" (frame center)	3.5" (caster arm)	2.53" (frame center)	3" (frame center)	3.25" (frame base)	2.55" (frame center)	1.5" (anti-tip wheels)					
TURNING RADIUS ⁵	20.5"	20"	20"	22.5"	21.25"	19.75"	35.75"	21.25"	26.5"					
OVERALL LENGTH	35.5" without foot riggings	35.5" without foot riggings	35.5" without foot riggings	36" without foot riggings	34.74" without foot riggings	35.6" without foot riggings	36" without foot riggings	34.74" without foot riggings	38.25" without foot riggings					
BASE WIDTH	24.4"	24"	24"	25.875"	23.19"	26.25"	25"	23.19"	29.25"					
Seating Sizes:	TRU-Balance [®] 3	TRU-Balance [®] 2	TRU-Balance [®] 3	TRU-Balance [®] 2	TRU-Balance [®] 3	TRU-Balance [®] 2	TRU-Balance [®] 2	TRU-Balance [®] 2 HD Tilt	TRU-Balance [®] 3 HD Tilt & Recline	TRU-Balance [®] 2	TRU-Balance [®] 3	TRU-Balance [®] 2	TRU-Balance [®] 2 HD Tilt	
SYNERGY [®] / STATIC	W: 10-22" D: 10-22"	W: 10-22" D: 10-22"	W: 12-22" D: 12-22"	W: 10-22" D: 10-22"	W: 12-22" D: 12-22"	W: 10-24" D: 10-24"	W: 10-20" D: 10-20"	W: 20-28" D: 20-28"	W: 20-32" D: 20-28"	W: 10-22" D: 10-20"	W: 12-22" D: 12-22"	W: 10-20" D: 10-20"	W: 20-32" D: 20-28"	
POWER TILT	W: 12-22" D: 12-22"	W: 14-22" D: 14-22"	W: 12-22" D: 12-22"	W: 14-22" D: 14-22"	W: 12-22" D: 12-22"	W: 14-24" D: 14-24"	W: 14-20" D: 14-20"	W: 20-28" D: 20-28"	W: 20-32" D: 20-25"	W: 14-22" D: 14-20"	W: 12-22" ³ D: 12-22" ³	W: 14-20" D: 14-20"	W: 20-32" D: 20-28"	
LIFT & TILT	W: 16-22" D: 14-22"	N/A	W: 12-22" D: 12-22"	N/A	W: 12-22" D: 12-22"	W: 16-20" D: 16-20"	W: 16-20" D: 16-20"	N/A	W: 16-24" D: 16-25"	N/A	W: 12-22" ³ D: 12-22" ³	N/A	N/A	
Seat-to-Floor Heights:	TRU-Balance [®] 3	TRU-Balance [®] 2	TRU-Balance [®] 3	TRU-Balance [®] 2	TRU-Balance [®] 3	TRU-Balance [®] 2	TRU-Balance [®] 2	TRU-Balance [®] 2 HD Tilt	TRU-Balance [®] 3 HD Tilt & Recline	TRU-Balance [®] 2	TRU-Balance [®] 3	TRU-Balance [®] 2	TRU-Balance [®] 2 HD Tilt	
SYNERGY [®] / STATIC ⁸	15.9-17.9"	15.9-17.9"	16.5-18.5"	15.9-17.9"	16.5-18.5"	18-20"	16.5-17.5"	16.5-18.5"	17.5-19.5"	16.5-18"	16.5-18.1"	16.5-17.5"	16.5-18.5"	
POWER TILT ⁸	17.5"-19.5"	17.3-19.3"	17.5-19.5"	17.3-19.3"	17.5-19.5"	18.4-20.4" (16.6" with Super Low ¹¹)	16.875"	18.2-20.9"	18.5-20.5"	16.5-18"	18-19.6"	16.875"	18.125-20.125"	
LIFT & TILT ⁸	17.5-19.5"	N/A	18-20"	N/A	18-20"	20" (18" with Super Low ¹¹)	18.3"	N/A	17.75-19.75"	N/A	18.5-20.1"	N/A	N/A	
MANUAL TILT / RECLINE ¹⁰	Yes	Yes	Yes	Yes	Yes	Yes	Yes	No	Yes	Yes	Yes	Yes	No	
BATTERY SIZE ⁶	NF-22	NF-22	NF-22	NF-22	NF-22 or Group 24	U-1	Group 24	Group 24	Group 24	Group 24	U-1	Group 24	Group 24	
BATTERY WEIGHT ¹⁴	38 lbs.	38 lbs.	38 lbs.	38 lbs.	38 lbs. - 52 lbs.	24.5 lbs.	52 lbs.	52 lbs.	52 lbs.	52 lbs.	24.5 lbs.	52 lbs.	52 lbs.	
AVAILABLE ELECTRONICS ¹²	75A Q-Logic 2 NE 75A Q-Logic 2 NE+ 100A Q-Logic 2 EX	75A Q-Logic 2 NE 75A Q-Logic 2 NE+ 90A Q-Logic 2 EX	75A Q-Logic 2 NE 75A Q-Logic 2 NE+ 90A Q-Logic 2 EX	75A Q-Logic 2 NE 75A Q-Logic 2 NE+ 90A Q-Logic 2 EX	75A Q-Logic 2 NE 75A Q-Logic 2 NE+ 90A Q-Logic 2 EX ¹³	70A PG VR2 70A Q-Logic 2 EX	75A Q-Logic 2 NE 75A Q-Logic 2 NE+ 100A Q-Logic 2 EX	75A Q-Logic 2 NE 75A Q-Logic 2 NE+ 90A Q-Logic 2 EX	75A Q-Logic 2 NE 75A Q-Logic 2 NE+ 90A Q-Logic 2 EX	75A Q-Logic 2 NE 75A Q-Logic 2 NE+ 90A Q-Logic 2 EX	70A Q-Logic 2 NE 70A Q-Logic 2 NE+ 70A Q-Logic 2 EX	90A VR2 6-key 100A Q-Logic 2 EX		
BATTERY CHARGER	8A Off-board	8A Off-board	8A Off-board	8A Off-board	8A Off-board	5A Off-board	8A Off-board	8A Off-board	8A Off-board	8A Off-board	5A Off-board	8A Off-board		
MOTOR PACKAGES	2-Pole Mid-Wheel 6 [®]	4-Pole 5 mph ¹ or 4-Pole 6 mph ²	4-Pole 6 mph	4-Pole 6 mph ¹ or 4-Pole 8 mph ²	2-Pole Glide 4 mph ¹	4-Pole 4.7 mph ¹	4-Pole 6 mph ¹ or 4-Pole 8 mph ²	2-Pole 4 mph	4-Pole 4.5 mph					
WEIGHT CAPACITY ⁷	300 lbs.	300 lbs.	300 lbs.	300 lbs.	300 lbs. ⁹	450 lbs.	300 lbs.	300 lbs. ⁹	600 lbs.					
BASE WEIGHT	138.6 lbs.	138 lbs.	138 lbs.	147 lbs.	112 lbs.	143.5 lbs.	129 lbs.	104.5 lbs.	195 lbs.					
MEDICARE CODE COVERAGE - For more information on Medicare code coverage, please consult our Product Planning and Reimbursement Center.														
	Group 3: Standard (K0848/K0849), Single Power (K0856), Multiple Power (K0861)	Group 3: Standard (K0848/K0849), Single Power (K0856/K0857), Multiple Power (K0861)	Group 3: Standard (K0848/K0849), Single Power (K0856), Multiple Power (K0861)	Group 3: Standard (K0848/K0849), Single Power (K0856/K0857), Multiple Power (K0861)	Group 2: Standard (K0822/K0823), Single Power (K0835/K0836)	Group 3: Heavy Duty (K0850/K0851), Single Power HD (K0858), Multiple Power HD (K0862)	Group 3: Standard (K0848/K0849), Single Power (K0856), Multiple Power (K0861)	Group 2: Standard (K0822/K0823), Single Power (K0835)	Group 3: Heavy Duty (K0850/K0851), Very Heavy Duty (K0852/K0853), Single Power HD (K0858), Single Power Very Heavy Duty (K0860), Multiple Power Very HD (K0863)					

1) Standard
2) Optional
3) Requires HD Suspension
4) Speed varies with user weight, terrain type, battery charge, battery condition and tire pressure.
5) Without front riggings

6) Battery capacity may change when adding power positioning systems.
7) Weight capacity is dictated by the selection of seating.
8) All measurements +/- 1/8" with 18" x 18" seat, fixed towers, 300 lbs. weight capacity and solid tires (add 3/8" with pneumatic tires). Widths may increase seat-to-floor height. Contact Customer Service for details. Listed measurements are in the lowest position; does not include elevating system unless specified.

9) 250 lbs. weight capacity with TRU-Balance[®] Systems
10) The Synergy[®] Manual Tilt weight capacity is 75 lbs. and maximum dimensions are 14" W x 14" D. Maximum dimensions of the Manual Recline vary by power base and seating system. Call for details.
11) Requires Group 34 batteries

12) All Quantum Rehab[®] units can be ordered with specialty controls
13) Required with high-speed motors
14) Battery weight may vary +/- 3 lbs. based on manufacturer.

The information contained herein is correct at the time of publication. We reserve the right to alter specifications without prior notice.

(US) 866-800-2002 • (Canada) 888-570-1113
www.quantumrehab.com • www.ilevel.rehab